






Código	Curso Cilindro (mm)	Força daN Pressão à 150bar Inicial	Força daN Pressão à 150bar Final*	L K=40 (mm)	L min. (mm)	Vol. inicial (cm³)	Kg
PNRG-0,5-010	10	471,2	636,2	60	50	12,1	0,317
PNRG-0,5-015	15	471,2	666,7	70	55	16,0	0,344
PNRG-0,5-020	20	471,2	686,5	80	60	20,0	0,373
PNRG-0,5-025	25	471,2	700,4	90	65	23,9	0,395
PNRG-0,5-032	32	471,2	714,2	104	72	29,5	0,432
PNRG-0,5-038	38	471,2	722,8	116	78	34,3	0,463
PNRG-0,5-050	50	471,2	734,6	140	90	43,8	0,527
PNRG-0,5-063	63	471,2	743,0	166	103	54,1	0,590
PNRG-0,5-075	75	471,2	748,4	190	115	63,6	0,650
PNRG-0,5-080	80	471,2	750,2	200	120	67,5	0,677
PNRG-0,5-100	100	471,2	755,8	240	140	83,4	0,780
PNRG-0,5-125	125	471,2	760,5	290	165	103,2	0,908


* Força Final Isotérmica a 20°C, curso totalmente atuado.




PNB-54-038




PNB-65-038




PNB-55-038



PNB-32-038



PNB-57-038



A PRODTY é detentora de patentes nacionais e internacionais, que cobrem características de seus produtos.